


renova roof drain type 63 T clamp ring, 345 mm, DN 70

Part number: 630049
 GTIN: 4001636630049
 Rebate group: 10



Description:

renova roof drain type 63 T clamp ring, 345 mm, DN 70
 conforming to DIN EN 1253

installed by pushing into the bore of pipe, usually without removing the existing roof drain, with stainless steel clamp ring to secure all single-ply membranes

specification:

- multi ribbed seal
- domed grating
- temporary blanking plate

material:

polypropylene, UV-stabilized
 rubber co-moulding

DN 70 fits B.S. 68 mm, 82 mm version available

Flow rates tested to DIN EN 1253:

| Nominal diameter | Min. flow rate according to norm | Water level according to norm | Flow rate at water level 5 mm | Flow rate at water level 15 mm | Flow rate at water level 25 mm | Flow rate at water level 35 mm | Flow rate at water level 45 mm | Flow rate at water level 55 mm | Flow rate at water level 65 mm | Flow rate at water level 75 mm |
|------------------|----------------------------------|-------------------------------|-------------------------------|--------------------------------|--------------------------------|--------------------------------|--------------------------------|--------------------------------|--------------------------------|--------------------------------|
| DN 70 | 1.70 l/s | 35.00 mm | 0.80 l/s | 3.60 l/s | 6.80 l/s | 9.70 l/s | 12.90 l/s | 13.30 l/s | 13.50 l/s | 13.60 l/s |

Spare parts:

620866 domed grating/gravel guard type 63 T, d